

## FILTRO "Y" ACERO FUNDIDO A BRIDAS ASA 150

– 300 – 600

### Materiales

DIAMETRO	CUERPO	CANASTO STD	BUJE-TAPA	ESPARRAGOS
½" a 1.1/2"	ASTM A 216 Gr.WCB	MALLA 30/30 304 SS	ASTM.A 105	N/P
2"			ASTM. A 216 Gr. WCB	ASTM. A193 Gr. B7 ASTM. A194 Gr. 2H
2.1/2" a 4"		CHAPA PERF. AGUJ. 3 MM		
5" a 12"				

### Datos Físicos

#### A BRIDAS ASA 150 RF

#### A BRIDAS ASA 300 RF


Diam. Pulg.	Dimensiones			Presión máxima	
	A mm	B mm	C Pulg.	Vapor saturado Kg/cm2	A 65° Kg/cm2
½"	161	75	½"	17	28
¾"	"	"	"	"	"
1"	187	102	"	"	"
1.1/4"	226	115	"	"	"
1.1/2"	230	"	"	"	"
2"	255	150	"	"	"
2.1/2"	302	155	¾"	"	"
3"	354	205	"	"	"
4"	420	270	1"	"	"
5"	530	320	1.1/4"	"	"
6"	565	370	1.1/2"	"	"
8"	561	325	2"	"	"
10"	635	450	"	15	19
12"	815	540	"	"	"

Diam. Pulg.	Dimensiones			Presión máxima	
	A mm	B mm	C Pulg.	Vapor Saturado Kg/cm2	A 65° Kg/cm2
½"	168	75	½"	42	51
¾"	"	"	"	"	"
1"	194	102	"	"	"
1.1/4"	233	115	"	"	"
1.1/2"	237	"	"	"	"
2"	265	150	"	"	"
2.1/2"	309	155	¾"	"	"
3"	364	205	"	"	"
4"	436	270	1"	"	"
5"	553	320	1.1/4"	"	"
6"	588	370	1.1/2"	"	"
8"	586	325	2"	"	"

## A BRIDAS ASA 600 RF

Diam. Pulg.	Dimensiones			Presión máxima	
	A mm	B mm	C Pulg.	Vapor saturado Kg/cm2	A 65° C Kg/cm2
1/2"	<b>181</b>	<b>75</b>	1/2"	<b>80</b>	<b>105</b>
3/4"	"	"	"	"	"
1"	<b>207</b>	<b>102</b>	"	"	"
1.1/4"	<b>246</b>	<b>115</b>	"	"	"
1.1/2"	<b>250</b>	"	"	"	"
2"	<b>275</b>	<b>150</b>	"	"	"
2.1/2"	<b>312</b>	<b>155</b>	3/4"	"	"
3"	<b>377</b>	<b>205</b>	"	"	"
4"	<b>449</b>	<b>270</b>	1"	"	"

1/2" a 1.1/2"



2" a 12"

