

FILTRO "Y"

ACERO FUNDIDO ASTM A 216 A ROSCA O SOCKTWELD


Materiales

DIAMETRO	CUERPO	CANASTO STD..	BUJE TAPA	JUNTA	ESPARRAGOS
1/2"-3/4"-1"	ASTM A 216	MALLA 30/30 AISI 304	ASTM A 105	TEFLON	N/P.
1.1/4"-1.1/2"-2"					
2.1/2"-3"-4"	Gr. WCB	MALLA 16/60 AISI 304	ASTM A 216 Gr. WCB	LIBRE DE AMIANTO	ASTM A 193 B7 ASTM A 194 2H


Datos Fisicos

DIAM.	DIMENSIONES			PRESION MAXIMA	
	A mm	B mm	C mm	VAPOR SATURADO Bar	A 38 ° Bar
1/2"	98	70	1/2"	113	153
3/4"	111	70	1/2"	113	153
1"	111	70	1/2"	113	153
1.1/4"	134	90	1/2"	78	102
1.1/2"	148	98	1/2"	78	102
2"	175	120	1/2"	78	102
2.1/2"	195	135	3/4"	78	102
3"	230	165	3/4"	78	102
4"	285	205	1"	78	102

Corte Filtro "Y" 1/2" a 2"



Corte Filtro "Y" 2.1/2"-4"



Rango de Presión y Temperatura

